

# DVP-600

## Fusion Splicer

### Features

- 8 Sec celerity fusion
- Apply diversified quartz fiber
- Select manifold splice program
- Auto check fiber end-face
- 2.5 inch color LCD screen
- Adjusting parameters automatically
- Small volume, Light weight, in house and outside
- Languages selectable



### Specification

- Applicable Fiber.....SM, MM, DS, NZDS, EDF and EXF etc. Fiber
- Fiber cleaved length.....16mm(Standard)
- Average fusion loss.....0.1dB(SM),0.05dB(MM)
- Environment Condition.....Temperature -10℃ ~ +50℃, Humidity 0 ~ 95% (RH), altitude 0 ~4000meter
- Heater.....40Sec(Standard) , Select heating time seed the environment temperature
- Sleeve applicable length.....60mm, 40mm and round robin minimize protection sleeve
- Measurement.....128mm (W) ×135mm (D) ×155mm(H)
- Weight.....1.1Kg

### Standard Accessories

Battery/Charger, DC Power Cord, AC Power Cord, Spare Electrodes, Instruction Manual, Carrying Case, Cooling Salver, COM Cord, Software CD, Fiber Cleaving Tool, Coat Stripper



Address: A1403 Shanghui Edifice, No.11 Dinghuaimen Ave  
Nanjing, China (Post Code: 210036)

Tel: +86-25-86223907, 86223917, 86223927 Fax: +86-25-86223927  
http://www.njdvp.com E-mail: dvp@njdvp.com